




Product Description

1. Dual seal configuration
2. Balanced design
3. Independent of direction of rotation
4. For stepped shafts
5. Rotary unit with multiple springs
6. Pumping device available for increased efficiency in circulation (B740F-D)

Technical Features

1. Versatile torque transmission available
2. Capable of self cleaning
3. Multifaceted application usage
4. Pumping device to increase efficiency in circulation for media with higher viscosity available
5. Short installation length available
6. Suitable for media with low solids content
7. EN 12756 (For connection dimensions d_1 up to 100 mm)




Note: The item numbers as depicted above are based on our technical experience and knowledge and are placed in the chronological order of their assembly procedure.

Item	Part no.	Description
1.1	472.1	Seal face
1.2	472.2	Seal face
1.3	474	Thrust ring
1.4	485	Drive collar
1.5	477	Spring
1.6	904	Set screw
1.7	412.1	O-ring
1.8	412.2	O-ring
2	475.1	Seat (G9)
3	412.3	O-ring
4	475.2	Seat (G9)
5	412.4	O-ring

DIN 24250

Torque Transmission



$d_2 \geq 105$ mm VIA 4 set screws with cone points. (standard arrangement)

Typical Industrial Applications

API & ISO Pumps	hydrocarbons
Acids (some)	Low abrasive media
Aqueous solutions	Low solids media
Boiler feed pumps	Oil & gas
Chemical	Petrochemical
Fertiliser	Poor lubrication media
Highly viscous hydrocarbons	Power plant technology
Hot water applications	Refining technology
Light volatile	Toxic & hazardous media

Performance Capabilities

Sizes	d_1 = Upto 100 mm (Upto 4.000")
Single spring	d_1 = max. 100 mm (Upto 4.000")
Pressure	p_1 = 80 bar (1160 PSI) for d_1 = 14 ... 100 mm,
	p_1 = 25 bar (363 PSI) for d_1 = 100 ... 200 mm,
	p_1 = 16 bar (232 PSI) for d_1 > 200 mm
Temperature	t = -50 °C...+220 °C (-58 °F...+428 °F)
Speed	20 m/s (66 ft/s)

Permissible Axial Movement

d_1 up to 100 mm:	± 0.5 mm
d_1 up to 100 mm:	± 2.0 mm

Standards


EN 12756

Materials


Seal face	Silicon carbide (Q1, Q2), Carbon graphite antimony impregnated (A), Aluminium oxide (V), Special cast CrMo steel (S)
Seat G9	Carbon graphite antimony impregnated (A), Carbon graphite resin impregnated (B), Silicon carbide (Q1*, Q2*)
Secondary seals	EPDM (E), NBR (P), FKM (V), FFKM (K)
Springs	CrNiMo steel (G)
Metal parts	CrNiMo steel (G), Duplex (G1)

* Cannot be combined with seal face made of S

Stationary Seats



G6
(EN 12756)



G4

Dimensional Data

Dimensions in millimeter

d ₁	d ₂	d ₃	d ₆	d ₇	d ₈	d ₁₁	d ₁₂	d _s	l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀	l ₁₂	l ₁₄	l ₁₅	l ₁₆	l ₂₈	l ₃₁	m _x	R
14	18	33	21.0	25	3	20.5	24.6	-	73	18	53	26.5	1.5	4	8.5	17.5	10	7.5	6.5	5.6	1.5	5	6.6	17	M5	1.2
16	20	35	23.0	27	3	22.0	28.0	-	73	18	53	26.5	1.5	4	8.5	17.5	10	7.5	8.5	7.5	1.5	5	6.6	17	M5	1.5
18	22	37	27.0	33	3	24.0	30.0	42	76	20	53	26.5	2	5	9	19.5	11.5	8.5	9	8	1.5	5	7.5	17	M5	1.5
20	24	39	29.0	35	3	29.5	35.0	44	76	20	53	26.5	2	5	9	19.5	11.5	8.5	8.5	7.5	1.5	5	7.5	17	M5	1.5
22	26	41	31.0	37	3	29.5	35.0	45	76	20	53	26.5	2	5	9	19.5	11.5	8.5	8.5	7.5	1.5	5	7.5	17	M5	1.5
24	28	43	33.0	39	3	32.0	38.0	47	77	20	54	27	2	5	9	19.5	11.5	8.5	8.5	7.5	1.5	5	7.5	17.5	M6	1.5
25	30	45	34.0	40	3	32.0	38.0	49	77	20	54	27	2	5	9	19.5	11.5	8.5	8.5	7.5	1.5	5	7.5	17.5	M6	1.5
28	33	48	37.0	43	3	36.0	42.0	51	77	20	54	27	2	5	9	19.5	11.5	8.5	10	9	1.5	5	7.5	17.5	M6	1.5
30	35	50	39.0	45	3	39.2	45.0	54	77	20	54	27	2	5	9	19.5	11.5	8.5	11.5	10.5	1.5	5	7.5	17.5	M6	1.5
32	38	55	42.0	48	3	42.2	48.0	59	79	20	56	28	2	5	9	19.5	11.5	8.5	11.5	10.5	1.5	5	7.5	18.5	M6	1.5
33	38	55	42.0	48	3	44.2	50.0	59	79	20	56	28	2	5	9	19.5	11.5	8.5	12	10.5	1.5	5	7.5	18.5	M6	1.5
35	40	57	44.0	50	3	46.2	52.0	61	80	20	57	28.5	2	5	9	19.5	11.5	8.5	12	11	1.5	5	7.5	19	M6	1.5
38	43	60	49.0	56	4	49.2	55.0	65	85	23	57	28.5	2	6	9	22	14	10	11.3	10.3	2	6	9	19	M6	1.5
40	45	62	51.0	58	4	52.2	58.0	66	85	23	57	28.5	2	6	9	22	14	10	11.8	10.8	2	6	9	19	M6	1.5
43	48	65	54.0	61	4	53.3	62.0	69	85	23	57	28.5	2	6	9	22	14	10	13.2	12	2	6	9	19	M6	2.5
45	50	67	56.0	63	4	55.3	64.0	71	84	23	56	28	2	6	9	22	14	10	12.8	11.6	2	6	9	19.5	M6	2.5
48	53	70	59.0	66	4	59.7	68.4	75	84	23	56	28	2	6	9	22	14	10	12.8	11.6	2	6	9	19.5	M6	2.5
50	55	72	62.0	70	4	60.8	69.3	76	93	25	63	31.5	2.5	6	9	23	15	10.5	12.8	11.6	2	6	9.5	19.5	M6	2.5
53	58	79	65.0	73	4	63.8	72.3	83	97	25	67	33.5	2.5	6	9	23	15	12	13.5	12.3	2	6	11	23.5	M8	2.5
55	60	81	67.0	75	4	66.5	75.4	85	97	25	67	33.5	2.5	6	9	23	15	12	14.5	13.3	2	6	11	23.5	M8	2.5
58	63	84	70.0	78	4	69.5	78.4	88	104	25	74	37	2.5	6	9	23	15	12	14.5	13.3	2	6	11	24.5	M8	2.5
60	65	86	72.0	80	4	71.5	80.4	95	104	25	74	37	2.5	6	9	23	15	12	14.5	13.3	2	6	11	24.5	M8	2.5
63	68	89	75.0	83	4	74.5	83.4	93	109	25	79	39.5	2.5	6	9	23	15	12	14.2	13.3	2	6	11	24.5	M8	2.5
65	70	91	77.0	85	4	76.5	85.4	95	98	25	68	34	2.5	6	9	23	15	12	14.2	13	2	6	11	23.5	M8	2.5
70	75	99	83.0	92	4	83.0	92.0	105	112.5	28	76.4	38.2	2.5	7	9	26	18	12.5	14.9	13.7	2	6	11.3	25.5	M8	2.5
75	80	104	88.0	97	4	90.2	99.0	109	112.5	28	76.4	38.2	2.5	7	9	26	18	12.5	14.2	13	2	6	11.3	25.5	M8	2.5
80	85	109	95.0	105	4	95.2	104.0	114	112.5	28	76	38	3	7	9	26.2	18.2	12.5	15.2	14	2	6	11.3	25	M8	2.5
85	90	114	100.0	110	4	100.2	109.0	119	112.5	28	76	38	3	7	9	26.2	18.2	13	16.2	15	2	6	12	25.5	M8	2.5
90	95	119	105.0	115	4	105.2	114.0	124	112.5	28	76	38	3	7	9	26.2	18.2	15	16	14.8	2	6	14	25	M8	2.5
95	100	124	110.0	120	4	111.6	120.3	129	110.5	28	76	38	3	7	9	25.2	17.2	15	16	14.8	2	6	14	25	M8	2.5
100	105	129	115.0	125	4	114.5	123.3	134	110.5	28	76	38	3	7	9	25.2	17.2	15	17	15.8	-	-	14	25.5	M8	2.5
105	115	148	122.2	134.3	5	-	-	153	122	32	82	41	2	10	-	30	20	15	17	15.8	-	-	14	31.5	M8	-
110	120	153	128.2	140.3	5	-	-	158	122	32	82	41	2	10	-	30	20	-	-	-	-	-	-	31.5	M8	-
115	125	158	136.2	148.3	5	-	-	163	122	32	82	41	2	10	-	30	20	-	-	-	-	-	-	31.5	M8	-
120	130	163	138.2	150.3	5	-	-	168	122	32	82	41	2	10	-	30	20	-	-	-	-	-	-	31.5	M8	-
125	135	168	142.2	154.3	5	-	-	173	122	32	82	41	2	10	-	30	20	-	-	-	-	-	-	31.5	M8	-
130	140	173	146.2	158.3	5	-	-	178	122	32	82	41	2	10	-	30	20	-	-	-	-	-	-	31.5	M8	-
135	145	178	152.2	164.3	5	-	-	183	122	32	82	41	2	10	-	30	20	-	-	-	-	-	-	31.5	M8	-
140	150	183	156.2	168.3	5	-	-	188	122	32	82	41	2	10	-	30	20	-	-	-	-	-	-	31.5	M8	-
145	155	191	161.2	173.3	5	-	-	196	133	34	93	46.5	2	10	-	30	20	-	-	-	-	-	-	35.5	M8	-
150	160	196	168.2	180.3	5	-	-	201	137	36	93	46.5	2	10	-	32	22	-	-	-	-	-	-	35.5	M8	-
155	165	201	173.2	185.3	5	-	-	206	141	38	93	46.5	2	12	-	34	24	-	-	-	-	-	-	35.5	M8	-
160	170	206	178.2	190.3	5	-	-	211	141	38	93	46.5	2	12	-	34	24	-	-	-	-	-	-	35.5	M8	-
165	175	211	183.2	195.3	5	-	-	216	141	38	93	46.5	2	12	-	34	24	-	-	-	-	-	-	35.5	M8	-
170	180	216	188.2	200.3	5	-	-	221	141	38	93	46.5	2	12	-	34	24	-	-	-	-	-	-	35.5	M8	-
175	185	221	193.2	205.3	5	-	-	226	141	38	93	46.5	2	12	-	34	24	-	-	-	-	-	-	35.5	M8	-
180	190	226	207.5	219.3	5	-	-	231	149	42	93	46.5	2	12	-	38	28	-	-	-	-	-	-	35.5	M8	-
185	195	231	212.5	224.3	5	-	-	236	149	42	93	46.5	2	12	-	38	28	-	-	-	-	-	-	35.5	M8	-
190	200	236	217.5	229.3	5	-	-	241	149	42	93	46.5	2	12	-	38	28	-	-	-	-	-	-	35.5	M8	-
195	205	245	222.5	234.3	5	-	-	250	151	43	95	47.5	2	12	-	38	28	-	-	-	-	-	-	-	M10	-
200	210	250	227.5	239.3	5	-	-	255	151	43	95	47.5	2	12	-	38	28	-	-	-	-	-	-	-	-	-

d₁ > 200 on request

inch size available from size 0.625 to 7.875

Note: Additional technical & dimensional information will be provided on request.

The specifications, drawings, images etc included in this catalogue are intended to be generic and must be interpreted as equivalent or functionally equivalent, more specifically the performance capabilities mentioned in this catalogue is based on optimum values, however the performance of the product is dependent on size, material of construction, media, pressure, temperature, sliding velocity etc and it shall vary from size to size or application to application. Customers are requested to consult with Sealmatic before employing the product from this catalogue for any application.